

Material Safety Data Sheet

Ink Cartridge(BK) (MSDS:H086039-00-04-NA-E)

Section 1. Chemical product and company identification

Common name : Ink Cartridge(BK) (H086039-00)

Material uses : Ink

Supplier/ Manufacturer : NK Works Co., Ltd, 579-1, Umehara, Wakayama-shi, 640-8550, Japan

Phone: +81 73 456 3969 Fax: +81 73 456 3991

Email: msds@noritsu.com

In case of emergency : CHEMTREC, U.S: (800)424-9300 International: (703)527-3887

Section 2. Hazards identification

Physical state : Liquid. Emergency overview : Warning!

CANCER HAZARD

CONTAINS MATERIAL WHICH CAN CAUSE CANCER

CAUSES EYE AND SKIN IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.

Avoid contact with skin and clothing. Wash thoroughly after handling. Risk of cancer

depends on duration and level of exposure.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes : Irritating to eyes.

Skin : Irritating to skin. May cause sensitization by skin contact.

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Potential chronic health

effects

: CARCINOGENIC EFFECTS: Classified + (Proven.) by NIOSH [Carbon Black]. Classified

: 2B (Possible for human.) by IARC [Carbon Black]. Classified A4 (Not classifiable for

human or animal.) by ACGIH [Carbon Black]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.

Medical conditions : Repeated exposure to a highly toxic material may produce general deterioration of health

aggravated by overexposure by an accumulation in one or many human organs.

See toxicological Information (section 11)

Section 3. Composition, Information on Ingredients

							CAS number	% by weight
United States Glycerin, (Glycerol) Carbon Black							56-81-5 1333-86-4	About 10 1 - 5
Canada Carbon Black							1333-86-4	1 - 5
Mexico	Classification							
	UN number	IDLH	Н	F	R	Special		
Glycerin, (Glycerol)	Not regulated.	-	0	1	0	•	56-81-5	About 10
Carbon Black	Not regulated.	1750 mg/m₃	2	0	0		1333-86-4	1 - 5

This material is classified hazardous under OSHA regulations in the United States, the WHMIS Controlled Product Regulation in Canada and the NOM-018-STPS-2000 in Mexico.

See Chapters 8, 11 and 14 for details.

Date of issue : 12/14/2012 Page: 1/6

Ink Cartridge (BK) (H086039-00-04-NA-E)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse.

Thoroughly clean shoes before reuse. Get medical attention immediately.

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. Get medical attention if symptoms

appear.

Notes to physician : No specific antidote. Medical staff must contact Poison Control Center.

Section 5. Fire fighting measures

Flammability of the product: May be combustible at high temperature.

Flash point : Closed cup: >100°C (212°F). (Pensky-Martens.)

Products of combustion : These products are carbon oxides (CO, CO 2), nitrogen oxides (NO, NO2...).

Fire hazards in presence of : Slightly flammable to flammable in presence of open flames, sparks and static **various substances** discharge.

Non-flammable in presence of heat.

Because of the large amount of water contained in the product, the product might be

combustible only after partial or complete evaporation.

Fire fighting media and instructions

: Use an extinguishing agent suitable for surrounding fires.

No specific hazard.

Special protective equipment for fire- fighters

: Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8).

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

and sewers.

Methods for cleaning up
 If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage : Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8. Exposure Controls, Personal Protection

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the

airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are

proximal to the work-station location.

Personal protection Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Recommended:Safety glasses.

Date of issue : 12/14/2012 Page: 2/6

Ink Cartridge (BK) (H086039-00-04-NA-E)

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an

approved standard if a risk assessment indicates this is

necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of

the selected respirator.

: Chemical-resistant, impervious gloves or gauntlets complying with an **Hands**

approved standard should be worn at all times when handling chemical

products if a risk assessment indicates this is necessary. >8 hour(s) (breakthrough time): Disposable vinyl gloves.

: Personal protective equipment for the body should be selected based on Skin/Body

the task being performed and the risks involved and should be approved

by a specialist before handling this product.

Body: Recommended:Lab coat.

of a large spill

Personal protection in case: Safety glasses, goggles or face shield. Impervious gloves. Full suit. Boots. Wear

MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full

protective gear.

Product name Exposure limits

United States

ACGIH TLV (United States, 9/2004). Glycerin, (Glycerol)

TWA: 10 mg/m 38 hour(s). Form: Mist OSHA PEL (United States, 8/1997).

TWA: 5 mg/m 3 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m 38 hour(s). Form: All forms.

Carbon Black ACGIH TLV (United States, 1/2004).

> TWA: 3.5 mg/m 3 8 hour(s). Form: All forms. NIOSH REL (United States, 12/2001). TWA: 3.5 mg/m 3 10 hour(s). Form: All forms. TWA: 0.1 MGPHM3 10 hour(s). Form: All forms.

OSHA PEL (United States, 8/1997).

TWA: 3.5 mg/m 3 8 hour(s). Form: All forms.

Canada

Carbon Black ACGIH TLV (Canada, 2003).

TWA: 3.5 mg/m 3 8 hour(s). Form: All forms.

Mexico

NOM-010-STPS (Mexico, 12/1999). Glycerin, (Glycerol)

CPT: 10 mg/m₃ 8 hour(s). Form: Mist

NOM-010-STPS (Mexico, 12/1999). Carbon Black

CCT: 7 mg/m₃ 15 minute(s). Form: Smoke CPT: 3.5 mg/m₃ 8 hour(s). Form: Smoke

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Physical state : Liquid. Color : Black. Odor : Slightly. : 8.8-10.2 PH

Boiling/condensation point: The lowest known value is 100°C (212°F) (Water).

Melting/freezing point : <0°C (32°F) Specific gravity : 1.08 (Water = 1)

Vapor pressure : The highest known value is 2.3 kPa (17.5 mm Hg) (at 20°C) (Water).

Vapor density : The highest known value is 0.62 (Air = 1) (Water).

Ionicity (in water) : Amphoteric. (Water).

Dispersion properties : See solubility in water, methanol, acetone.

Solubility : Miscible in water.

Date of issue : 12/14/2012 Page: 3/6





Ink Cartridge (BK) (H086039-00-04-NA-E)

Section 10. Stability and reactivity

Stability and reactivity : The product is stable.

Incompatibility with various: Reactive with oxidizing agents.

substances

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

Toxicity data

Ingredient name
Carbon Black
Carbon Black
Carbon Black
Carbon Black
LD50
Result
>15400 mg/kg
Oral
Rat

Acute Effects

Eyes : Irritating to eyes.

Skin : Irritating to skin. May cause sensitization by skin contact.

InhalationIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Potential chronic health

effects

: CARCINOGENIC EFFECTS: Classified + (Proven.) by NIOSH [Carbon Black]. Classified 2B (Possible for human.) by IARC [Carbon Black]. Classified A4 (Not classifiable for

human or animal.) by ACGIH [Carbon Black]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.

Section 12. Ecological information

Ecotoxicity data : Not applicable.

Products of degradation: These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO_{2...}).

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Classification:

Mexico / TDG/ DOT/ IMDG/ IATA: Not regulated.

NAERG : Not available.

Label

Not applicable.

Additional information

Not applicable.

Section 15. Regulatory information

United States

HCS Classification : Irritating material

Sensitizing material

Carcinogen

U.S. Federal regulations : TSCA 8(b) inventory: All components listed.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Glycerin, (Glycerol); Carbon Black. SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Glycerin, (Glycerol): Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Carbon

Black: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard.

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

Clean air act (CAA) 112 accidental release prevention: No products were found. Clean air act (CAA) 112 regulated flammable substances: No products were found. Clean air act (CAA) 112 regulated toxic substances: No products were found.

State regulations

: Pennsylvania RTK: Glycerin, (Glycerol): (generic environmental hazard); Carbon Black:

(generic environmental hazard).

Massachusetts RTK: Glycerin, (Glycerol); Carbon Black.

New Jersey: Carbon Black

WARNING: This product contains a chemical known to the State of California to cause

cancer.

Ingredient name Cancer Reproductive No significant risk Maximum acceptable dosage

Level Level

Carbon Black Yes. No. No. No. No.

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (VERY TOXIC).

Class D-2B: Material causing other toxic effects (TOXIC).

DSL: All components listed.

Mexico

Classification :



International regulations International lists

: All components listed are listed on major international inventories or exempted from being listed in Australia (AICS), Europe (EINECS/ELINCS), Korea (TCCL), Japan (METI/MOL), Philippines (RA6969).

Date of issue : 12/14/2012 Page: 5/6


Section 16. Other information

Label Requirements : CANCER HAZARD

CONTAINS MATERIAL WHICH CAN CAUSE CANCER

CAUSES EYE AND SKIN IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)



References : ANSI Z400.1, MSDS Standard, 2001. -Manufacturer's Material Safety Data Sheet. -

29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG. -Canada Gazette Part II, Vol. 122, No. 2 Registration SOR/88-64 31 December, 1987 Hazardous Products Act "Ingredient Disclosure List". - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2002. - Official Mexican Standards NOM-018-

STPS-2000 and NOM-004-SCT2-1994.

Date of issue : 12/14/2012

Version : 5

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.